



## Eco Summitec SERIES

### GENERAL DESCRIPTION

ECO SUMMITEC represents a major breakthrough in Quick Setting Ink technology.

ECO SUMMITEC was formulated with newly developed high performance varnishes made of high-solubility & high-molecular phenol resins and with high density and excellent water-resistant pigments..

ECO SUMMITEC is available in 2.5kg Vac Pac Cans, 2.0kg Incline Cartridges and 200kg Drums.

### FEATURES

- Excellent rub-resistance, fast setting & drying time
- Soy Based & Laser Safe
- Approved by American Soy Association
- Manufactured to ISO9001 & ISO14001 Standards
- Low VOC (3-4%)

### SPECIFICATIONS

ITEM	QUICK-SET ECO			
	MAGENTA	YELLOW	CYAN	BLACK
T.V	9.0	9.0	9.0	9.0
D.M	37.0±1	39.0±1	37.0±1	38.0±1
SETTING	3.0	3.0	3.0	3.0
DRYING	3.0	3.0	3.0	3.0
NON-SKINNING	20↑	20↑	20↑	20↑
VISCOSITY	280± 10	220± 10	300± 10	240± 10

### TEST METHOD

- T.V : Ink-O-Meter 400RPM 60 sec/32°C
- D.M(Flow) : Spread-O-Meter 60 sec/25°C
- Setting(Min) : RI-Tester 4seperated roller (0.075cc)
- Drying(Hr) : Drum type drying tester on coated paper
- Non-Skinning(Hr) : Drying time on glass at 25°C
- Viscosity(Poise) : Laray Viscometer at 25°C



## A.S. INK & CHEMICAL CO., LTD

ROOM NO.405 WOOLIM E-BIZ CENTER, 16, YANGPYEONGDONG 3-GA, YOUNGDEUNGPO-KU, SEOUL, KOREA

PHONE: 82-2-2164-8220/4 FAX: 82-2-2164-8225 E-MAIL: [asink@asink.com](mailto:asink@asink.com)