



SWISS BRILLIANCE IN COATING

The right Inline GALACRYL® waterbased Primer for perfect Inline UV-varnishing

Product reference	82.280.02	82.280.03
	<u>Inline gloss Primer</u>	<u>Inline matt Primer</u>
Properties of the varnish		
Viscosity DIN 4mm/23° C	approx. 60 s	approx. 55 s
Solid content	46%	46%
Properties of the varnish film		
Blocking properties	medium	medium
Film laminating		
UV-varnishing	•	•
Instructions	Stir well before use	Stir very well before use
Features	UV-varnish must overlap Primer Not suitable for spot UV-appliances	Suitable for spot UV-appliances
Type of machine		
Varnishing machine		
Sheet-fed offset		
Coating unit/ Anilox roller	•	•
Dampening unit	•	•
Web offset		
Coating unit		
Flexographic press		
Anilox roller	•	•

For more information about single products or specialties, please contact us and we will send you the specific technical data sheet.

Technical inquiry:

A. Ceppi	Tel. ++41 (0)44 712 62 62	Mobil ++41 (0)79 431 41 58
J. Siegrist	Tel. ++41 (0)44 712 62 69	Mobil ++41 (0)79 341 50 47
S. Scheidegger	Tel. ++41 (0)44 712 62 66	Mobil ++41 (0)79 824 75 15
O. Schuler	Tel. ++41 (0)44 712 62 76	Mobil ++41 (0)79 549 90 78
D. Reitter	Tel. ++41 (0)44 712 62 22	Mobil ++41 (0)76 571 42 86