



SWISS BRILLIANCE IN COATING

The right GALACRYL[®] additive for perfect waterbased appliance

Product Reference	8801	8803
	Slip- and anti-blocking additive	Retarding agent
Dosage	Add 0,5 - max. 1% into GALACRYL [®] varnishes.	Add 1 - max. 4% into GALACRYL [®] varnishes.
Instructions	For foil blocking, we recommend preliminary test.	Check stack on a regular base concerning blocking, temperature and appearance.
Features	Improves slip- and anti-blocking properties. Recommended for 2-sided jobs.	Slows down drying of the varnish. Reduces cracking of the varnish. Caution: may reduces blocking properties.

For more information about single products or specialties, please contact us and we will send you the specific technical data sheet.

Technical inquiry:

A. Ceppi	Tel. ++41 (0)44 712 62 62	Mobil ++41 (0)79 431 41 58
J. Siegrist	Tel. ++41 (0)44 712 62 69	Mobil ++41 (0)79 341 50 47
S. Scheidegger	Tel. ++41 (0)44 712 62 66	Mobil ++41 (0)79 824 75 15
O. Schuler	Tel. ++41 (0)44 712 62 76	Mobil ++41 (0)79 549 90 78
D. Reitter	Tel. ++41 (0)44 712 62 22	Mobil ++41 (0)76 571 42 86