



SWISS BRILLIANCE IN COATING

The right high viscose WESSCO® UV-varnish for perfect Offline or Inline UV-varnishing

WESSCO® 3200 series: High viscose, offline, low odour, Benzophenon-free, slightly irritating according to OECD

Product reference	3201	3202	3203	3205	3210
Properties of the varnish					
Viscosity DIN 4mm/23° C	approx. 65 s	approx. 150 s	approx. 260 s	approx. 95 s	approx. 4,2 Pa.s.
Reactivity m/min ¹⁾	50	55	55	50	55
Properties of the varnish film					
Surface Slip	good	good	good	good	good
Glueability					
Foil Blocking					
Hotmelt-Glueability					
Instructions	Stir well before use	Stir well before use	Stir very well before use	Stir well before use	Stir well before use
Type of machine					
Varnishing machine	Normal				
	Reverse				
Sheet-fed offset	Coating unit/ Anilox roller				
	Inking unit	•	•		•
	Dampening unit	•		•	
Web offset	Coating unit				
Flexographic press	Anilox roller	•		•	

¹⁾ Lab-reference values: per lamp 80 W/cm

For more information about single products or specialties, please contact us and we will send you the specific technical data sheet.

Technical inquiry:

A. Ceppi	Tel. ++41 (0)44 712 62 62	Mobil ++41 (0)79 431 41 58
J. Siegrist	Tel. ++41 (0)44 712 62 69	Mobil ++41 (0)79 341 50 47
S. Scheidegger	Tel. ++41 (0)44 712 62 66	Mobil ++41 (0)79 824 75 15
O. Schuler	Tel. ++41 (0)44 712 62 76	Mobil ++41 (0)79 549 90 78
D. Reitter	Tel. ++41 (0)44 712 62 22	Mobil ++41 (0)76 571 42 86