



SWISS BRILLIANCE IN COATING

The right WESSCO® UV-varnish for perfect silkscreen UV-varnishing

WESSCO® 3400 series: Silkscreen, low odour, Benzophenon-free, slightly irritating according to OECD

Product reference	34.238.15
Properties of the varnish	
Viscosity DIN 4mm/23° C	approx. 65 s
Reactivity m/min ¹⁾	50
Properties of the varnish film	
Surface Slip	good
Glueability	
Foil Blocking	
Hotmelt-Glueability	
Instructions	Stir very well before use
Type of machine	
Varnishing machine	Normal
	Reverse
Sheet-fed offset	Coating unit/ Anilox roller
	Inking unit
	Dampening unit
Web offset	Coating unit
Flexographic press	Anilox roller
Silkscreen	•

¹⁾ Lab-reference values: per lamp 80 W/cm

For more information about single products or specialties, please contact us and we will send you the specific technical data sheet.

Technical inquiry:

A. Ceppi	Tel. ++41 (0)44 712 62 62	Mobil ++41 (0)79 431 41 58
J. Siegrist	Tel. ++41 (0)44 712 62 69	Mobil ++41 (0)79 341 50 47
S. Scheidegger	Tel. ++41 (0)44 712 62 66	Mobil ++41 (0)79 824 75 15
O. Schuler	Tel. ++41 (0)44 712 62 76	Mobil ++41 (0)79 549 90 78
D. Reitter	Tel. ++41 (0)44 712 62 22	Mobil ++41 (0)76 571 42 86