



SCHWISS BRILLIANZ IN COATING

The right WESSCO® UV-varnish for perfect Inline UV-varnishing on Hybrid ink

WESSCO® 4200 series: Inline on Hybrid ink, low odour, Benzophenon-free, slightly irritating according to OECD

Product reference		4202 Hybrid	4203 Hybrid	4205 Hybrid
Properties of the varnish				
Viscosity DIN 4mm/23° C		approx. 60 s	approx. 100 s	approx. 100 s
Reactivity m/min ¹⁾		70	80	80
Properties of the varnish film				
Surface Slip		good	medium	good
Glueability			•	
Foil Blocking			•	
Hotmelt-Glueability				
Instructions		Stir well before use	Stir very well before use	Stir well before use
Type of machine				
Varnishing machine		Normal		
		Reverse		
Sheet-fed offset	Coating unit/ Anilox roller	•	•	•
	Inking unit			
	Dampening unit			
Web offset	Coating unit			
Flexographic press	Anilox roller	•	•	•

¹⁾ Lab-reference values: per lamp 80 W/cm

For more information about single products or specialties, please contact us and we will send you the specific technical data sheet.

Technical inquiry:

A. Ceppi	Tel. ++41 (0)44 712 62 62	Mobil ++41 (0)79 431 41 58
J. Siegrist	Tel. ++41 (0)44 712 62 69	Mobil ++41 (0)79 341 50 47
S. Scheidegger	Tel. ++41 (0)44 712 62 66	Mobil ++41 (0)79 824 75 15
O. Schuler	Tel. ++41 (0)44 712 62 76	Mobil ++41 (0)79 549 90 78
D. Reitter	Tel. ++41 (0)44 712 62 22	Mobil ++41 (0)76 571 42 86