



SWISS BRILLIANCE IN COATING

## The right WESSCO® UV adhesives for film laminating for perfect in-line label UV laminating

**WESSCO® series 6600:** very low odour, benzophenone-free, slightly irritating to skin according to OECD

Product Designation	6601	66.220.01
<b>Technical Data</b>	High viscosity	Low viscosity
Viscosity DIN 4mm/23° C	(ca. 250 s)	160 s +- 10s
Viscosity DIN 6mm/23° C	60 s +- 5 s	-
Reactivity m/min <sup>1)</sup>	30	30
<b>Film</b>		
OPP with corona treatment <sup>2)</sup>	yes	yes
Acetate	no	no
OPP with acrylic coating	yes <sup>3)</sup>	yes <sup>3)</sup>
Polyester	no	no
PET	no	no
<b>Processing</b>		
Application	Flexo Anilox system	Flexo Anilox system
Further processing of laminate	immediately	immediately
<b>Notes</b>		

<sup>1)</sup> laboratory reference value: 80 W/cm per lamp <sup>2)</sup> surface tension: at least 38 mN/m <sup>3)</sup> must be checked prior to use

For more detailed information on individual products or special products, we will be glad to send you the respective technical data sheets.

Application technology:

A. Ceppi	Tel ++41 (0)44 712 62 62	Mobile +41 (0)79 431 41 58
J. Siegrist	Tel ++41 (0)44 712 62 69	Mobile +41 (0)79 341 50 47
S. Scheidegger	Tel ++41 (0)44 712 62 66	Mobile +41 (0)79 824 75 15
O. Schuler	Tel. ++41 (0)44 712 62 76	Mobil ++41 (0)79 549 90 78
D. Reitter	Tel. ++41 (0)44 712 62 22	Mobil ++41 (0)76 571 42 86