



SWISS BRILLIANCE IN COATING

The right WESSCO® UV- Additive for perfect UV- appliance

Product Reference	1915	1935	2160
	Wetting agent	Anti-penetration additive	Slip- and anti blocking additive
Dosage	Add 3 - max. 5% into WESSCO® varnishes.	Add 5% into WESSCO® varnishes.	Add 0.5 - max.1.0 % into WESSCO® varnishes.
Instructions	Not to be used with glueable and foil blockable WESSCO® varnishes.	Add additive before production. Looses its properties after 24 hours.	Do preliminary test for foil blocking.
Features	Improves wetting properties over difficult surfaces.	Reduces the penetration and the greying effect of WESSCO® varnishes into the coating of the paper / board.	Improves the slip- and blocking properties of WESSCO® varnishes. Recommended for 2-sided jobs.

For more information about single products or specialties, please contact us and we will send you the specific technical data sheet.

Technical inquiry:

A. Ceppi	Tel. ++41 (0)44 712 62 62	Mobil ++41 (0)79 431 41 58
J. Siegrist	Tel. ++41 (0)44 712 62 69	Mobil ++41 (0)79 341 50 47
S. Scheidegger	Tel. ++41 (0)44 712 62 66	Mobil ++41 (0)79 824 75 15
O. Schuler	Tel. ++41 (0)44 712 62 76	Mobil ++41 (0)79 549 90 78
D. Reitter	Tel. ++41 (0)44 712 62 22	Mobil ++41 (0)76 571 42 86